

ROLL'FRESH



Temperature holding banquet trolley **in refrigerated link**. Built of food-quality stainless steel. Insulation of the walls and door with rock wool. Interior completely shelved with press-drawn back and sliders. Space between sliders : 71 mm. Solid stainless steel door opening through 270° with compressible gasket.

Non-marking shockproof surround. 4 swivelling wheels including 2 with brakes, Ø 160 mm with stainless steel cover on cabinet GN 2/1 and Ø 125 mm with polyamide cover on cabinet GN 1/1. Protection index IP 25, allowing cleaning with a low pressure jet.

Control panel with sensitive button. The refrigerating unit is located in the lower part. Refrigerating gas R134a. Voltage 230 V. Ventilated evaporator with air blown in at the upper rear part and collected at the centre of the ceiling. Defrosting evaporation tray. Cabinet supplied with bracket for temperature recorder (recorder optional).



ROLL'FRESH	Rating (W)	Overall dim. l x W x h (mm)	Reference
GN 1/1, 15 levels with stainless steel door	200	528 x 821 x 1750	507 286
GN 2/1, 15 levels with stainless steel door	300	733 x 941 x 1786	507 296

OPTIONS	Reference
temperature recorder	229 527
extra-cost for lock and key	701 961
extra-cost for 4 swivel stainless steel wheels Ø 125 mm including 2 brakes to replace wheels with polyamid cover	702 190



Refrigerating unit located in the lower part



Roll'Fresh supplied with bracket for temperature recorder.



Temperature recorder, ref. 229 527