



TM65

Mid-level Report

AG3: 3-1Gn Designline Ambient Gantry 1150mm (Self Help)

Assessment Date 05/11/2025

Manufacturer CED Fabrications

Contact Email sales@cedlimited.com

Metrics	
<div><div>Embodied Carbon</div><div>188 kgCO2e</div></div>	<div><div>Embodied Carbon Footprint</div><div><div><div></div></div><div><div>Material</div><div>Manufacture</div><div>Transport</div><div>Refrigerant</div><div>Waste</div><div>Disposal</div></div></div></div>
Product Information	
Capacity of equipment/size (kW; m3; litres; etc.)	N/A
Product weight (kg)	15 kg
Material % breakdown for at least 95% of the product weight? (Y/N)	Y
Product service life (years)	10
If refrigerant based, type of refrigerant used and GWP	N/A
Refrigerant charge (kg)	N/A
Energy consumption of the factory* per unit of product	17 kWh
Location of manufacture*	N/A
Product complexity category	3

Embodied carbon results (kg CO2e) – breakdown	
A1: Material extraction	94 kgCO2e
A2: Transport	12 kgCO2e
A3: Manufacturing	19 kgCO2e
A4: Transport to site	0.59 kgCO2e
A5: Construction	N/A
B1: Refrigerant leakage during use	0 kgCO2e
B2: Maintenance (if information given by manufacturer)	N/A
B3: Repair	15 kgCO2e
B4: Replacement	N/A
B5: Refurbishment	N/A
B6: Operational energy	N/A
B7: Operational water	N/A
C1: Refrigerant leakage when decommissioning	0 kgCO2e
C2: Transport	0.2 kgCO2e
C3: Waste processing	5 kgCO2e
C4: Disposal	0.07 kgCO2e
Embodied carbon results (kg CO2e) – without refrigerant leakage	
A1–C4 without buffer factor (excluding B1, C1)	144 kgCO2e
A1–C4 with buffer factor (excluding B1, C1)	188 kgCO2e
Embodied carbon result (kg CO2e) – refrigerant leakage only	
B1 (refrigerant leakage during use) + C1 (refrigerant leakage at end of life)	N/A
Embodied carbon result with 'mid-level' calculation method – total	
Result of 'mid-level' calculation method	188 kgCO2e
Assumptions	
A1: Material carbon coefficient source	CIBSE TM65, Table 2.1
B1: Refrigerant annual leakage rate (%)	N/A
C1: Refrigerant end of life recovery rate (%)	N/A
B3: Materials replaced as part of repair (%)	3
C4: Percentage of product going to landfill (%)	55