



TM65

Mid-level Report

PC9FBHTD + PAF1: Designline HT Cold Drop In Patisserie, self service, fixed back, 900mm + (Airflow Kit In-Out Customer Side)

Assessment Date 08/12/2025

Manufacturer CED Fabrications

Contact Email sales@cedlimited.com

Metrics

Embodied Carbon

2,334 kgCO2e

Embodied Carbon Footprint



Product Information

Capacity of equipment/size (kW; m3; litres; etc.)	N/A
Product weight (kg)	173 kg
Material % breakdown for at least 95% of the product weight? (Y/N)	Y
Product service life (years)	10
If refrigerant based, type of refrigerant used and GWP	Propane (R 290), No refrigerant, 0.04 kgCO2e
Refrigerant charge (kg)	0.41 kg
Energy consumption of the factory* per unit of product	200 kWh
Location of manufacture*	N/A

Embodied carbon results (kg CO2e) – breakdown

A1: Material extraction	1,019 kgCO2e
A2: Transport	137 kgCO2e
A3: Manufacturing	217 kgCO2e
A4: Transport to site	7 kgCO2e
A5: Construction	N/A
B1: Refrigerant leakage during use	0.33 kgCO2e
B2: Maintenance (if information given by manufacturer)	N/A
B3: Repair	358 kgCO2e
B4: Replacement	N/A
B5: Refurbishment	N/A
B6: Operational energy	N/A
B7: Operational water	N/A
C1: Refrigerant leakage when decommissioning	0.02 kgCO2e
C2: Transport	2 kgCO2e
C3: Waste processing	54 kgCO2e
C4: Disposal	0.84 kgCO2e

Embodied carbon results (kg CO2e) – without refrigerant leakage

A1–C4 without buffer factor (excluding B1, C1)	1795 kgCO2e
A1–C4 with buffer factor (excluding B1, C1)	2333 kgCO2e

Embodied carbon result (kg CO2e) – refrigerant leakage only

B1 (refrigerant leakage during use) + C1 (refrigerant leakage at end of life)	0 kgCO2e
---	----------

Embodied carbon result with 'mid-level' calculation method – total

Result of 'mid-level' calculation method	2,334 kgCO2e
--	--------------

Assumptions

A1: Material carbon coefficient source	CIBSE TM65, Table 2.1
B1: Refrigerant annual leakage rate (%)	N/A
C1: Refrigerant end of life recovery rate (%)	N/A
B3: Materials replaced as part of repair (%)	55
C4: Percentage of product going to landfill (%)	55

