

# TM65

## Mid-level Report




GACP5 + GAG5: Glide Plain Top Ambient Cupd. + Amb. Gantry (Self Help & Ass. Serve) 5-1 Gn

Assessment Date 14/04/2026

Manufacturer CED Fabrications

Contact Email sales@cedlimited.com



| Product Information  |         |
|--|---------|
| Capacity of equipment/size (kW; m3; litres; etc.)                  | N/A     |
| Product weight (kg)  | 149 kg  |
| Material % breakdown for at least 95% of the product weight? (Y/N) | Y       |
| Product service life (years)                                       | 10      |
| If refrigerant based, type of refrigerant used and GWP             | N/A     |
| Refrigerant charge (kg)  | N/A     |
| Energy consumption of the factory* per unit of product             | 172 kWh |
| Location of manufacture*   | N/A     |
| Product complexity category  | 3       |

| Embodied carbon results (kg CO2e) — breakdown                                 |                       |
|---|-----------------------|
| A1: Material extraction   | 597 kgCO2e            |
| A2: Transport   | 118 kgCO2e            |
| A3: Manufacturing   | 186 kgCO2e            |
| A4: Transport to site   | 6 kgCO2e              |
| A5: Construction  | N/A                   |
| B1: Refrigerant leakage during use  | 0 kgCO2e              |
| B2: Maintenance (if information given by manufacturer)                        | N/A                   |
| B3: Repair  | 61 kgCO2e             |
| B4: Replacement   | N/A                   |
| B5: Refurbishment   | N/A                   |
| B6: Operational energy  | N/A                   |
| B7: Operational water   | N/A                   |
| C1: Refrigerant leakage when decommissioning                                  | 0 kgCO2e              |
| C2: Transport   | 2 kgCO2e              |
| C3: Waste processing  | 47 kgCO2e             |
| C4: Disposal  | 0.73 kgCO2e           |
| Embodied carbon results (kg CO2e) — without refrigerant leakage               |                       |
| A1–C4 without buffer factor (excluding B1, C1)                                | 1017 kgCO2e           |
| A1–C4 with buffer factor (excluding B1, C1)                                   | 1323 kgCO2e           |
| Embodied carbon result (kg CO2e) — refrigerant leakage only                   |                       |
| B1 (refrigerant leakage during use) + C1 (refrigerant leakage at end of life) | N/A                   |
| Embodied carbon result with 'mid-level' calculation method — total            |                       |
| Result of 'mid-level' calculation method                                      | 1,359 kgCO2e          |
| Assumptions   |                       |
| A1: Material carbon coefficient source  | CIBSE TM65, Table 2.1 |
| B1: Refrigerant annual leakage rate (%)                                       | N/A                   |
| C1: Refrigerant end of life recovery rate (%)                                 | N/A                   |
| B3: Materials replaced as part of repair (%)                                  | 12                    |
| C4: Percentage of product going to landfill (%)                               | 55                    |