



Ventilation / Display Performance Considerations


- 1) Area in which display is to be sited must have a minimum room floor area no less than 2 sq m.
- 2) Install over a sealed floor or ventilated floor void.
- 3) Do not site the display within 2m of ceiling mounted air conditioning grilles.
- 4) Do not site the display beneath a high level of direct sunlight.
- 5) Display will operate in a 24 hour environment.




PLAN VIEW



END VIEW



FRONT VIEW
(CUSTOMER SIDE)



REAR VIEW
(OPERATOR SIDE)

13A PLUG TOP & 3m CABLE ENTRY
POWER SUPPLY: 13A, 230V, 1.66kW

| COLOUR FINISH (FRONT & SIDES) | OPTION CODE |
|-------------------------------|-------------|
| MERLIN GREY | STANDARD |
| OCEAN BLUE | GBLUECHA3 |
| GOOSEWING LIGHT GREY | GGREYCHA3 |
| POPPY RED | GPREDCHA3 |
| WHITE | GWHITCHA3 |
| FOREST GREEN / HERITAGE | GGRENCHA3 |
| BUTTERMILK CREAM / HONESTY | GCREMCHA3 |
| BLACK | GBLAKCHA3 |
| WALNUT | GWALNCHA3 |
| BEECH | GBEECCHA3 |
| OAK | GOAKCHA3 |
| SATIN S/STEEL | GSSTLCHA3 |


APPROX. UN-CRATED
WEIGHT OF UNIT: 168Kg



CED FABRICATIONS LTD
UNITS A1-A4, FALCON COURT
CLAYTON BUSINESS PARK
CLAYTON-LE-MOORS
HYNDBURN
LANCASHIRE BB5 5JD

This drawing and information herein is confidential to CED Fabrications Ltd. It is issued in confidence that it will not be disclosed to any third party in part or in whole without permission from CED FABRICATIONS Ltd.

© CED FABRICATIONS LTD



DESCRIPTION:

GLIDE DINING CARTS
3-1 ASSISTED SERVICE COLD MULTIDECK
(REAR DOORS - R290 REFRIGERANT)
+ S/STEEL FOLDING SOLID TRAY SLIDE

SCALE: 1 : 25@A4 REV No: A

PRODUCT
CODE:

GMDR3ASHT
+ GSTS3