



# TM65

## Mid-level Report

GCW2HT + GADG2 + GPS2 + GTTS2: Glide Cold Deli (Inc. Rear Prep Shelf) - Cold Well + Amb. Deli Gantry + Rear Shelf (A.Serve) + S.Steel Tray Rail 2-1Gn

Assessment Date 09/04/2026

Manufacturer CED Fabrications

Contact Email sales@cedlimited.com

### Metrics

#### Embodied Carbon

**1,466** kgCO<sub>2</sub>e

#### Embodied Carbon Footprint



### Product Information

Capacity of equipment/size (kW; m3; litres; etc.)	N/A
Product weight (kg)	137 kg
Material % breakdown for at least 95% of the product weight? (Y/N)	Y
Product service life (years)	10
If refrigerant based, type of refrigerant used and GWP	No refrigerant, Propane (R 290), 0.04 kgCO <sub>2</sub> e
Refrigerant charge (kg)	0.285 kg
Energy consumption of the factory* per unit of product	158 kWh
Location of manufacture*	N/A
Product complexity category	3

Embodied carbon results (kg CO2e) – breakdown	
A1: Material extraction	686 kgCO2e
A2: Transport	108 kgCO2e
A3: Manufacturing	171 kgCO2e
A4: Transport to site	5 kgCO2e
A5: Construction	N/A
B1: Refrigerant leakage during use	0.23 kgCO2e
B2: Maintenance (if information given by manufacturer)	N/A
B3: Repair	110 kgCO2e
B4: Replacement	N/A
B5: Refurbishment	N/A
B6: Operational energy	N/A
B7: Operational water	N/A
C1: Refrigerant leakage when decommissioning	0.01 kgCO2e
C2: Transport	2 kgCO2e
C3: Waste processing	43 kgCO2e
C4: Disposal	0.68 kgCO2e
Embodied carbon results (kg CO2e) – without refrigerant leakage	
A1–C4 without buffer factor (excluding B1, C1)	1126 kgCO2e
A1–C4 with buffer factor (excluding B1, C1)	1464 kgCO2e
Embodied carbon result (kg CO2e) – refrigerant leakage only	
B1 (refrigerant leakage during use) + C1 (refrigerant leakage at end of life)	0 kgCO2e
Embodied carbon result with 'mid-level' calculation method – total	
Result of 'mid-level' calculation method	1,466 kgCO2e
Assumptions	
A1: Material carbon coefficient source	CIBSE TM65, Table 2.1
B1: Refrigerant annual leakage rate (%)	N/A
C1: Refrigerant end of life recovery rate (%)	N/A
B3: Materials replaced as part of repair (%)	23
C4: Percentage of product going to landfill (%)	55