

# TM65

## Mid-level Report



GMDR5ASHT + GTTS5: Glide Cold M.Deck - Rear Doors (Ass. Serve) + S.Steel Tray Rail 5-1Gn

Assessment Date 09/04/2026

Manufacturer CED Fabrications

Contact Email sales@cedlimited.com

Metrics

Embodied Carbon

3,388 kgCO2e

Embodied Carbon Footprint



Product Information

Capacity of equipment/size (kW; m3; litres; etc.)	N/A
Product weight (kg)	354 kg
Material % breakdown for at least 95% of the product weight? (Y/N)	Y
Product service life (years)	10
If refrigerant based, type of refrigerant used and GWP	No refrigerant, Propane (R 290), 0.04 kgCO2e
Refrigerant charge (kg)	0.715 kg
Energy consumption of the factory* per unit of product	410 kWh
Location of manufacture*	N/A
Product complexity category	3

Embodied carbon results (kg CO2e) — breakdown	
A1: Material extraction	1,610 kgCO2e
A2: Transport	280 kgCO2e
A3: Manufacturing	444 kgCO2e
A4: Transport to site	14 kgCO2e
A5: Construction	N/A
B1: Refrigerant leakage during use	0.57 kgCO2e
B2: Maintenance (if information given by manufacturer)	N/A
B3: Repair	139 kgCO2e
B4: Replacement	N/A
B5: Refurbishment	N/A
B6: Operational energy	N/A
B7: Operational water	N/A
C1: Refrigerant leakage when decommissioning	0.03 kgCO2e
C2: Transport	5 kgCO2e
C3: Waste processing	111 kgCO2e
C4: Disposal	2 kgCO2e

  

Embodied carbon results (kg CO2e) — without refrigerant leakage	
A1–C4 without buffer factor (excluding B1, C1)	2604 kgCO2e
A1–C4 with buffer factor (excluding B1, C1)	3385 kgCO2e

  

Embodied carbon result (kg CO2e) — refrigerant leakage only	
B1 (refrigerant leakage during use) + C1 (refrigerant leakage at end of life)	1 kgCO2e

  

Embodied carbon result with 'mid-level' calculation method — total	
Result of 'mid-level' calculation method	3,388 kgCO2e

  

Assumptions	
A1: Material carbon coefficient source	CIBSE TM65, Table 2.1
B1: Refrigerant annual leakage rate (%)	N/A
C1: Refrigerant end of life recovery rate (%)	N/A
B3: Materials replaced as part of repair (%)	11
C4: Percentage of product going to landfill (%)	55