



# TM65

## Mid-level Report

GEW2 + GADG2 + GSTS2: Glide Eutectic Cold Deli (No Rear Shelf) - Eut. Well + Amb.  
Deli Gantry (A.Serve) + S.Steel Tray Slide 2-1Gn

Assessment Date 08/04/2026

Manufacturer CED Fabrications

Contact Email sales@cedlimited.com

### Metrics

#### Embodied Carbon

**950** kgCO<sub>2</sub>e

#### Embodied Carbon Footprint



### Product Information

|  |         |
|--|---------|
| Capacity of equipment/size (kW; m3; litres; etc.)                  | N/A     |
| Product weight (kg)  | 109 kg  |
| Material % breakdown for at least 95% of the product weight? (Y/N) | Y       |
| Product service life (years)                                       | 10      |
| If refrigerant based, type of refrigerant used and GWP             | N/A     |
| Refrigerant charge (kg)  | N/A     |
| Energy consumption of the factory* per unit of product             | 126 kWh |
| Location of manufacture*   | N/A     |
| Product complexity category  | 3       |

**Embodied carbon results (kg CO2e) — breakdown**

|  |             |
|--|-------------|
| A1: Material extraction                                | 406 kgCO2e  |
| A2: Transport  | 86 kgCO2e   |
| A3: Manufacturing                                      | 136 kgCO2e  |
| A4: Transport to site                                  | 4 kgCO2e    |
| A5: Construction                                       | N/A         |
| B1: Refrigerant leakage during use                     | 0 kgCO2e    |
| B2: Maintenance (if information given by manufacturer) | N/A         |
| B3: Repair   | 43 kgCO2e   |
| B4: Replacement  | N/A         |
| B5: Refurbishment                                      | N/A         |
| B6: Operational energy                                 | N/A         |
| B7: Operational water                                  | N/A         |
| C1: Refrigerant leakage when decommissioning           | 0 kgCO2e    |
| C2: Transport  | 1 kgCO2e    |
| C3: Waste processing                                   | 34 kgCO2e   |
| C4: Disposal   | 0.53 kgCO2e |

**Embodied carbon results (kg CO2e) — without refrigerant leakage**

|  |            |
|--|------------|
| A1–C4 without buffer factor (excluding B1, C1) | 712 kgCO2e |
| A1–C4 with buffer factor (excluding B1, C1)    | 926 kgCO2e |

**Embodied carbon result (kg CO2e) — refrigerant leakage only**

|   |     |
|---|-----|
| B1 (refrigerant leakage during use) + C1 (refrigerant leakage at end of life) | N/A |
|---|-----|

**Embodied carbon result with 'mid-level' calculation method — total**

|  |            |
|--|------------|
| Result of 'mid-level' calculation method | 950 kgCO2e |
|--|------------|

**Assumptions**

|   |                       |
|---|-----------------------|
| A1: Material carbon coefficient source          | CIBSE TM65, Table 2.1 |
| B1: Refrigerant annual leakage rate (%)         | N/A                   |
| C1: Refrigerant end of life recovery rate (%)   | N/A                   |
| B3: Materials replaced as part of repair (%)    | 21                    |
| C4: Percentage of product going to landfill (%) | 55                    |

[CONTACT US](#)[WEBSITE](#)[SOCIAL](#)[hello@impact-loop.com](mailto:hello@impact-loop.com)[impact-loop.com](https://www.impact-loop.com)[LinkedIn](#)