

TM65

Mid-level Report



GWSHP5 + GWSHG5 + GSTS5: Glide (Wall Sited) Ceran Top H.Cupd + Hot Gantry (Self Help) + S.Steel Tray Slide 5-1Gn

Assessment Date 10/04/2026

Manufacturer CED Fabrications

Contact Email sales@cedlimited.com

Metrics

Embodied Carbon

1,645 kgCO2e

Embodied Carbon Footprint

- Material
- Manufacture
- Transport
- Refrigerant
- Waste
- Disposal

| Product Information | |
|--|---------|
| Capacity of equipment/size (kW; m3; litres; etc.) | N/A |
| Product weight (kg) | 174 kg |
| Material % breakdown for at least 95% of the product weight? (Y/N) | Y |
| Product service life (years) | 10 |
| If refrigerant based, type of refrigerant used and GWP | N/A |
| Refrigerant charge (kg) | N/A |
| Energy consumption of the factory* per unit of product | 202 kWh |
| Location of manufacture* | N/A |
| Product complexity category | 3 |

Embodied carbon results (kg CO2e) — breakdown

| | |
|--|-------------|
| A1: Material extraction | 754 kgCO2e |
| A2: Transport | 138 kgCO2e |
| A3: Manufacturing | 218 kgCO2e |
| A4: Transport to site | 7 kgCO2e |
| A5: Construction | N/A |
| B1: Refrigerant leakage during use | 0 kgCO2e |
| B2: Maintenance (if information given by manufacturer) | N/A |
| B3: Repair | 89 kgCO2e |
| B4: Replacement | N/A |
| B5: Refurbishment | N/A |
| B6: Operational energy | N/A |
| B7: Operational water | N/A |
| C1: Refrigerant leakage when decommissioning | 0 kgCO2e |
| C2: Transport | 2 kgCO2e |
| C3: Waste processing | 55 kgCO2e |
| C4: Disposal | 0.86 kgCO2e |

Embodied carbon results (kg CO2e) — without refrigerant leakage

| | |
|--|-------------|
| A1–C4 without buffer factor (excluding B1, C1) | 1264 kgCO2e |
| A1–C4 with buffer factor (excluding B1, C1) | 1643 kgCO2e |

Embodied carbon result (kg CO2e) — refrigerant leakage only

| | |
|---|-----|
| B1 (refrigerant leakage during use) + C1 (refrigerant leakage at end of life) | N/A |
|---|-----|

Embodied carbon result with 'mid-level' calculation method — total

| | |
|--|--------------|
| Result of 'mid-level' calculation method | 1,645 kgCO2e |
|--|--------------|

Assumptions

| | |
|---|-----------------------|
| A1: Material carbon coefficient source | CIBSE TM65, Table 2.1 |
| B1: Refrigerant annual leakage rate (%) | N/A |
| C1: Refrigerant end of life recovery rate (%) | N/A |
| B3: Materials replaced as part of repair (%) | 13 |
| C4: Percentage of product going to landfill (%) | 55 |

[CONTACT US](#)[WEBSITE](#)[SOCIAL](#)hello@impact-loop.comimpact-loop.com[LinkedIn](#)