



#### Ventilation / Display Performance Considerations


- 1) Area in which display is to be sited must have a minimum room floor area no less than 28 sq m.
- 2) Install over a sealed floor or ventilated floor void.
- 3) Do not site the display within 2m of ceiling mounted air conditioning grilles.
- 4) Do not site the display beneath a high level of direct sunlight.
- 5) Display will operate in a 24 hour environment.




PLAN VIEW



END VIEW



FRONT VIEW  
(CUSTOMER SIDE)



REAR VIEW  
(OPERATOR SIDE)

13A PLUG TOP & 3m CABLE ENTRY  
POWER SUPPLY: 13A, 230V, 1.73kW

COLOUR FINISH (FRONT & SIDES)	OPTION CODE
MERLIN GREY	STANDARD
OCEAN BLUE	GBLUEWSC3
GOOSEWING LIGHT GREY	GGREYWSC3
POPPY RED	GPREDWSC3
WHITE	GWHITWSC3
FOREST GREEN / HERITAGE	GGRENWSC3
BUTTERMILK CREAM / HONESTY	GCREMWSC3
BLACK	GBLAKWSC3
WALNUT	GWALNWSC3
BEECH	GBEECWSC3
OAK	GOAKWSC3
SATIN S/STEEL	GSSTLWSC3


APPROX. UN-CRATED  
WEIGHT OF UNIT: 159Kg



CED FABRICATIONS LTD  
UNITS A1-A4, FALCON COURT  
CLAYTON BUSINESS PARK  
CLAYTON-LE-MOORS  
HYNDBURN  
LANCASHIRE BB5 5JD

This drawing and information herein is confidential to CED Fabrications Ltd. It is issued in confidence that it will not be disclosed to any third party in part or in whole without permission from CED FABRICATIONS Ltd.

© CED FABRICATIONS LTD



#### DESCRIPTION:

GLIDE DINING CARTS  
3-1 SELF HELP COLD MULTIDECK  
(SHUTTER/F.BACK - R290 REFRIGERANT)

SCALE: 1 : 25 @ A4 REV No: A

PRODUCT  
CODE:

GMDF3RSHT