



«NF Hygiène Alimentaire» certificate issued by AFNOR Certification, certifies compliance with the standard NF031, available at www.marque-nf.com, for cleanability.



GASTRONORM

SLIDE BAR TROLLEYS

WELDED CONSTRUCTION

GN 1/1 bar slide trolleys

Reference	Levels	L (mm)	w (mm)	H (mm)	d (mm)	A (mm)	B (mm)	Weight (kg)
804 201	6	656	457	760	81	332	304	12
804 203	8	656	457	900	81	332	304	13
804 204	10	656	457	1650	144	332	304	15
804 206	15	656	457	1490	81	332	304	15
804 207	17	656	457	1650	81	332	304	16
804 209	20	656	457	1785	77	332	304	17

GN 2/1 bar slide trolleys

Reference	Levels	L (mm)	w (mm)	H (mm)	d (mm)	A (mm)	B (mm)	Weight (kg)
804 231	6	773	659	760	81	537	509	16
804 233	8	773	659	900	81	537	509	17
804 234	10	773	659	1650	144	537	508	17
804 236	15	773	659	1490	81	537	509	19
804 237	17	773	659	1650	81	537	509	21
804 239	20	773	659	1785	77	537	509	23

TECHNICAL SPECIFICATIONS:

- Food quality stainless steel construction.

Tube structure:

- Uprights 25 x 25 mm section stainless steel tube, thickness 12/10 mm.
- Spacers 30 x 20 mm section stainless steel tube, thickness 12/10 mm.

Slide bars:

- Bright stainless steel sheet thickness 12/10 mm.
- Continuous argon welds with no added metal.
- L-shaped with runner stops at each end.

Wheels:

- 4 swiveling wheels of which 2 are braked.
- Ø 125 mm with annular wheel guards.
- 4 swivelling wheels Ø 125 mm with polyamide cover including 2 braked, with ball bearings
- Annular bumpers.

Made to request: Trolley with closing bar for transport in a vehicle.

Maximum load: 20 kg per level, maximum 200 kg
Top shelf of stainless steel plate thickness 12/10 mm on 6 level models, thickness 15/10 mm on 8 level models.
Packed under plastic film.

