

TM65

Mid-level Report




KMDF4HT: 4-1Gn Kubus Cold Multideck 1525mm - Fixed Back (Self Help)

Assessment Date 29/10/2025

Manufacturer CED Fabrications

Contact Email sales@cedlimited.com

Metrics	
<div>Embodied Carbon</div> <div>2,322 kgCO2e</div>	<div>Embodied Carbon Footprint</div> <div><div><div>Material</div><div>Manufacture</div><div>Transport</div><div>Refrigerant</div><div>Waste</div><div>Disposal</div></div></div>
Product Information	
Capacity of equipment/size (kW; m3; litres; etc.)	N/A
Product weight (kg)	246 kg
Material % breakdown for at least 95% of the product weight? (Y/N)	Y
Product service life (years)	10
If refrigerant based, type of refrigerant used and GWP	Propane (R 290), No refrigerant, 0.04 kgCO2e
Refrigerant charge (kg)	0.645 kg
Energy consumption of the factory* per unit of product	285 kWh
Location of manufacture*	N/A
Product complexity category	3

Embodied carbon results (kg CO2e) – breakdown	
A1: Material extraction	1,056 kgCO2e
A2: Transport	195 kgCO2e
A3: Manufacturing	309 kgCO2e
A4: Transport to site	10 kgCO2e
A5: Construction	N/A
B1: Refrigerant leakage during use	0.52 kgCO2e
B2: Maintenance (if information given by manufacturer)	N/A
B3: Repair	135 kgCO2e
B4: Replacement	N/A
B5: Refurbishment	N/A
B6: Operational energy	N/A
B7: Operational water	N/A
C1: Refrigerant leakage when decommissioning	0.03 kgCO2e
C2: Transport	3 kgCO2e
C3: Waste processing	77 kgCO2e
C4: Disposal	1 kgCO2e
Embodied carbon results (kg CO2e) – without refrigerant leakage	
A1–C4 without buffer factor (excluding B1, C1)	1786 kgCO2e
A1–C4 with buffer factor (excluding B1, C1)	2321 kgCO2e
Embodied carbon result (kg CO2e) – refrigerant leakage only	
B1 (refrigerant leakage during use) + C1 (refrigerant leakage at end of life)	1 kgCO2e
Embodied carbon result with 'mid-level' calculation method – total	
Result of 'mid-level' calculation method	2,322 kgCO2e
Assumptions	
A1: Material carbon coefficient source	CIBSE TM65, Table 2.1
B1: Refrigerant annual leakage rate (%)	N/A
C1: Refrigerant end of life recovery rate (%)	N/A
B3: Materials replaced as part of repair (%)	4
C4: Percentage of product going to landfill (%)	55