



TM65

Mid-level Report

KMDR2HT+AF1: 2-1Gn Kubus Cold Multideck 825mm - Rear Doors (Self Help) +
(Airflow Kit In/Out Customer Side)

Assessment Date 30/10/2025

Manufacturer CED Fabrications

Contact Email sales@cedlimited.com

Metrics

Embodied Carbon
2,198 kgCO₂e

Embodied Carbon Footprint



Product Information

Capacity of equipment/size (kW; m3; litres; etc.)	N/A
Product weight (kg)	174 kg
Material % breakdown for at least 95% of the product weight? (Y/N)	Y
Product service life (years)	10
If refrigerant based, type of refrigerant used and GWP	Propane (R 290), No refrigerant, 0.04 kgCO ₂ e
Refrigerant charge (kg)	0.48 kg
Energy consumption of the factory* per unit of product	202 kWh
Location of manufacture*	N/A
Product complexity category	3

Embodied carbon results (kg CO2e) – breakdown	
A1: Material extraction	946 kgCO2e
A2: Transport	138 kgCO2e
A3: Manufacturing	219 kgCO2e
A4: Transport to site	7 kgCO2e
A5: Construction	N/A
B1: Refrigerant leakage during use	0.38 kgCO2e
B2: Maintenance (if information given by manufacturer)	N/A
B3: Repair	323 kgCO2e
B4: Replacement	N/A
B5: Refurbishment	N/A
B6: Operational energy	N/A
B7: Operational water	N/A
C1: Refrigerant leakage when decommissioning	0.02 kgCO2e
C2: Transport	2 kgCO2e
C3: Waste processing	55 kgCO2e
C4: Disposal	0.86 kgCO2e
Embodied carbon results (kg CO2e) – without refrigerant leakage	
A1–C4 without buffer factor (excluding B1, C1)	1691 kgCO2e
A1–C4 with buffer factor (excluding B1, C1)	2198 kgCO2e
Embodied carbon result (kg CO2e) – refrigerant leakage only	
B1 (refrigerant leakage during use) + C1 (refrigerant leakage at end of life)	0 kgCO2e
Embodied carbon result with 'mid-level' calculation method – total	
Result of 'mid-level' calculation method	2,198 kgCO2e
Assumptions	
A1: Material carbon coefficient source	CIBSE TM65, Table 2.1
B1: Refrigerant annual leakage rate (%)	N/A
C1: Refrigerant end of life recovery rate (%)	N/A
B3: Materials replaced as part of repair (%)	56
C4: Percentage of product going to landfill (%)	55