

Kubus (Drop In) Hot Patisserie



Patisserie (Fixed Back) Shown

900mm Self Help Hor Patisserie (Rear Doors)

ABOUT

The energy efficient heated patisserie is part of the Kubus range of 'drop in' serve over height patisseries - a choice of cold, hot & ambient commercial drop in displays that fit in servery counter worktops, to suit either self help or assisted service operations

This 13A Kubus heated drop in patisserie is ideal for the display of pre-heated cooked food, packaged, cartoned or unwrapped heated product. Kubus heated patisseries feature combined static & convected heat, 'point of sale' branding, with optimum product display provided through glazed side panels. The temperature of the 3 heated zones can be independently set by digital displays on the control panel, mounted in the counter front fascia/ rear panel, Product temperature is maintained at 70 - 75°C in +18°C ambient.

All drop in types have removable wire shelf grid covers for use with packaged produce. 40mm ticket strip mounting is fitted to each display level & high temperature 4000 kelvin LED lighting

FEATURES

Download All Technical Drawings From www.cedfabsltd.co.uk

Temperature Controls. The hot patisserie has 3x digital controllers, controlled by digital air temperature probes. Mains power is controlled by neon on/off switch. High temperature LED lighting is controlled by a neon on/off switch.



Model Sizes.

The Kubus self help or assisted service heated patisserie is an open or closed glass front drop in hot patisserie, available in 600mm, 900mm & 1200mm lengths

3 Tier Storage Capacity: 2 Tier Shelving & Large Base Display Deck.

The display features 2 no. heated shelves (adjustable in height) & a large heated display deck below. Each independently controlled zone has removable wire steel deck & shelf grid covers for use with packaged & cartoned heated produce. The display area is finished in food safe polyester coated steel.

LED Lighting. Canopy & shelf lighting in a low energy, high temperature LED fitting with opaque cover, colour 4000k.

Model Type: Self Help Drop In Hot Patisserie (Rear Doors).

Re-stocking access is by energy efficient, side hinged double glazed rear doors. Digital controls are mounted on the operator side/ rear base panel.

Model Type: Self Help Drop In Hot Patisserie (Fixed Back).

This heated patisserie is supplied as wall sited with a stainless steel back panel for positioning in an alcove, against a wall or back to back, forming a central island grab and go station! The digital controls are mounted on the customer side/ front base panel.

Model Type: Assisted Service Drop In Hot Patisserie (Rear Doors). Features a full glazed front screen that tilts forward for cleaning. Re-stocking access is through the energy efficient, side hinged double glazed rear doors.

Panoramic Glass Side & Top Panels. Top glass allows for serve over operation & side glass panels add natural lighting.

Model Dimensions. 600mm/ 900mm & 1200mm (L) x 750mm (D) x 843mm (H) Above Wktop/ 118mm (D) Below Worktop.

System Design. Static heating maintains food core, whilst convected heat surrounds the food surface. Stainless steel wire grid covers allow heat circulation around packaged food. Temperature Performance. Factory set for 70 - 75°C (+18°C ambient), each display

zone is adjustable. Finishes. Worktop, rear frame & tank in 430gd s/steel, toughened glass sides, roof/ front screen panels. Display area finished in food safe polyester coated steel, wire steel deck & shelf arid covers.


Power Supply. Supplied with 3m lead & 13 amp UK plug (13A 230V 50Hz) Low Maintenance. Easy clean surfaces and durable design ensure low maintenance.

Equipment Conformity. CE & UKCA Certified equipment.













Self Help (Drop In) Hot Patisserie (Rear Doors)

		-		
Code	Description	Dimensions (L x D x H mm)	Weight (kg)	Power Rating (kW)
KPH9D	Kubus Drop In S.Help Hot Patiss. (R.Doors) 600mm Kubus Drop In S.Help Hot Patiss. (R.Doors) 900mm Kubus Drop In S.Help Hot Patiss. (R.Doors) 1200mm	600x 750 x 843 900x 750 x 843 1200x 750 x 843	110 150 195	2.04 2.85 2.89

Model Description, Kubus Heated Drop In Patisserie, self service, 600mm/ 900mm/ 1200mm W x 750mm D x 843mm H (above deck). open front, hinged rear door, (2) polyester coated fixed angle shelves, (1) display deck, removable wire steel deck & shelf covers, static & convected heat, (3) variable heat zones, (3) control panel displays in 1x cassette (2M loom) for mounting in rear servery counter panel, (3) high temperature LED lighting (each tier), flat glass canopy & side glass, CE/UKCA, 3m lead/UK Plug (13A 230V 50 Hz). Tank Depth Below Worktop 118mm

Assisted Service (Drop In) Hot Patisserie (Rear Doors)

Code Descri	iption	Dimensions	Weight	Power
		$(L \times D \times H mm)$	(kg)	Rating (kW)
KPH6ASD Kubus	s Drop In A.Serve Hot Patiss. (R.Doors) 600mm	600x 750 x 843	117	2.04 2.85
KPH9ASD Kubus	s Drop In A.Serve Hot Patiss. (R.Doors) 900mm	900x 750 x 843	157	
KPH12ASD Kub	us Drop In A.Serve Hot Patiss. (R.Doors) 1200mm	1200x 750 x 843	204	2.89

Model Description. Kubus Heated Drop In Patisserie, assisted service, 600mm/ 900mm/ 1200mm W x 750mm D x 843mm H (above deck), closed front, full height flat glass front, hinged rear door, (2) polyester coated fixed angle shelves, (1) display deck, removable wire steel deck & shelf covers, static & convected heat, (3) variable heat zones, (3) control panel displays in 1x cassette (2M loom) for mounting in rear servery counter panel, (3) high temperature LÉD lighting (each tier), flat glass canopy & side glass, CE/UKCA, 3m lead/UK Plug (13A 230V 50 Hz). Tank Depth Below Worktop 118mm.



Self Help Hot Patisserie (Fixed Back)

Code	Description	Dimensions	Weight	Power
		$(L \times D \times H mm)$	(kg)	Rating (kW)
KPH6FBD	Kubus Drop In S.Help Hot Patiss. (F.Back) 600mm	n 600x 750 x 843	110	2.04
KPH9FBD	Kubus Drop In S.Help Hot Patiss. (F.Back) 900mm	900x 750 x 843	150	2.85
KPH12FB	Nubus Drop In S.Help Hot Patiss. (F.Back) 1200m	m 1200x 750 x 843	195	2.89

Model Description, Kubus Heated Drop In Patisserie, self service, wall sited, 600mm/ 900mm/ 1200mm W x 750mm D x 843mm H (above deck), open front, (1) fixed back panel, (2) polyester coated fixed angle shelves, (1) display deck, removable wire steel deck & shelf covers, static & convected heat, (3) variable heat zones, (3) control panel displays in 1x cassette (2M loom) for mounting in front of servery counter panel, flat glass canopy & sneeze screen, side glass, (3) high temperature LED lighting (each tier), CE/UKCA, 3m lead/UK Plug (13A 230V 50 Hz). Tank Depth Below Worktop 118mm.

DIMENSIONS

Tel: 01254 238 282

Operator

CED Fabrications Limited (Head Office), Units A1-A4 Falcon Court Clayton Business Park Clayton-Le-Moors, Hvndburn, Lancashire

