


# CONSTANT LEVEL UNIVERSAL TROLLEYS



## GENERAL CHARACTERISTICS:

- Food quality stainless steel construction.
- Top and cladding of 1 mm stainless steel plate.
- Interior lining of 0,8 mm with internal angles rounded for easy cleaning.
- Wheels with polyamide cover, ball bearings including 2 brakes.
- Handle of stainless steel tube  $\varnothing 25$  mm, polyamide end-pieces.
- Moulded polyethylene bumpers.
- For all containers  $\varnothing 120$  mm to  $\varnothing 280$  mm, adjusted by moving the  $\varnothing 20$  mm centring tubes, possibility of using for oval or other shapes of containers.
- Support plate made of stainless steel with 8 guide rollers.
- Level of presentation adjusted by adding or removing springs.
- Removable constant level dispensers.
- Maximum allowable load: 150 kg

## HEATING TROLLEYS:

- Powered up with illuminated On/Off switch.
- Heating started and adjusted by mechanical thermostat (from  $0^{\circ}$  to  $90^{\circ}\text{C}$ ).
- Stainless steel lid.
- Spiral cable with moulded plug (3G 1.5 mm<sup>2</sup>), length fully stretched 1.5 m.
- Heated by shielded stainless steel resistors.


### • Electrical specifications:

- Rating	: <b>1500 W</b>
- Nominal voltage	: <b>230V 1N ~</b>
- Frequency	: <b>50 Hz</b>
- Appliance classification	: <b>IP 44</b>
- Standards	: <b>EN 60335-1</b>
	: <b>EN 60335-2-49</b>

## NEUTRAL TROLLEYS:

- Optional stainless steel cover.

# CONSTANT LEVEL UNIVERSAL TROLLEYS



Description	Dimensions (L x W x H) mm	Reference
Universal neutral trolley	915 x 485 x 900	808 201
Universal heated trolley	915 x 485 x 900	808 205