



Ventilation / Display Performance Considerations

- 1) Area in which display is to be sited must have a minimum room volume no less than 33 cu m.
- 2) Install over a sealed floor or ventilated floor void.
- 3) Do not site the display within 2m of ceiling mounted air conditioning grilles.
- 4) Do not site the display beneath a high level of direct sunlight.
- 5) Display will operate in a 24 hour environment.




PLAN VIEW



END VIEW HEAVY DUTY CASTOR OPTION HDC12

FRONT VIEW (CUSTOMER SIDE)

DOUBLE GLAZED SLIDING FRONT DOORS



REAR VIEW (OPERATOR SIDE)

13A PLUG TOP & 2m LEAD  
POWER SUPPLY:  
13A, 230V, 1.66kW

CAPACITY: 330L


APPROX. UN-CRATED WEIGHT OF UNIT: 217Kg



CED FABRICATIONS LTD  
UNITS A1-A4, FALCON COURT  
CLAYTON BUSINESS PARK  
CLAYTON-LE-MOORS  
HYNDBURN  
LANCASHIRE BB5 5JD

This drawing and information herein is confidential to CED Fabrications Ltd. It is issued in confidence that it will not be disclosed to any third party in part or in whole without permission from CED FABRICATIONS Ltd.

© CED FABRICATIONS LTD



**DESCRIPTION:**

MONEY MAKER CHILLED MERCHANDISER  
1200mm 3 TIER SLIM (FRONT DOORS)  
HYDROCARBON TYPE-R290 REFRIGERANT  
WITH REAR HINGED DOOR OPTION

SCALE: 1 : 25@A4 REV No: A

PRODUCT CODE: MM1200SDHT+HDC12 + MMDR12S