


#### Ventilation / Display Performance Considerations

- 1) Area in which display is to be sited must have a minimum room floor area no less than 24 sq m.
- 2) Install over a sealed floor or ventilated floor void.
- 3) Do not site the display within 2m of ceiling mounted air conditioning grilles.
- 4) Do not site the display beneath a high level of direct sunlight.
- 5) Display will operate in a 24 hour environment.

DOUBLE GLAZED  
LOCKABLE HINGED  
FRONT DOORS



13A PLUG TOP  
& 2m LEAD

POWER SUPPLY:  
13A, 230V, 1.70kW  
CAPACITY: 700L

APPROX. UN-CRATED  
WEIGHT OF UNIT: 321Kg

LOCKABLE CASTORS  
WITH ADJUSTABLE  
CENTRE FOOT  
(SPANNER SUPPLIED)

REAR VIEW  
(OPERATOR SIDE)

#### DESCRIPTION:

MONEY MAKER CHILLED MERCHANDISER  
1500mm 4 TIER LARGE (HINGED DOORS)  
HYDROCARBON TYPE-R290 REFRIGERANT  
WITH REAR HINGED DOORS OPTION

SCALE: 1 : 2.5 @ A4 REV No: A

PRODUCT  
CODE:

MM15LHD  
+ MMDR15L



CED FABRICATIONS LTD  
UNITS A1-A4, FALCON COURT  
CLAYTON BUSINESS PARK  
CLAYTON-LE-MOORS  
HYNDBURN  
LANCASHIRE BB5 5JD

This drawing and information herein is confidential to CED Fabrications Ltd. It is issued in confidence that it will not be disclosed to any third party in part or in whole without permission from CED FABRICATIONS Ltd.

© CED FABRICATIONS LTD

