



TM65

Mid-level Report

Mid-level report for **MM1200SDHT + DGPSD: 3 Tier 1200 Slim Cold Merch. (Front Sliding Door) + (D. Glazed Side...**

Assessment Date 19/08/2025


Manufacturer CED Fabrications

Contact Email sales@cedlimited.com

Metrics

Embodied Carbon
2,505 kgCO₂e

Embodied Carbon Footprint



Product Information

| | |
|--|---|
| Capacity of equipment/size (kW; m3; litres; etc.) | N/A |
| Product weight (kg) | 263 kg |
| Material % breakdown for at least 95% of the product weight? (Y/N) | Y |
| Product service life (years) | 10 |
| If refrigerant based, type of refrigerant used and GWP | Propane (R 290), No refrigerant, 0.04 kgCO ₂ e |
| Refrigerant charge (kg) | 0.35 kg |
| Energy consumption of the factory* per unit of product | 82 kWh |
| Location of manufacture* | N/A |
| Product complexity category | 3 |

| Embodied carbon results (kg CO2e) – breakdown | |
|---|-----------------------|
| A1: Material extraction | 1,311 kgCO2e |
| A2: Transport | 209 kgCO2e |
| A3: Manufacturing | 85 kgCO2e |
| A4: Transport to site | 10 kgCO2e |
| A5: Construction | N/A |
| B1: Refrigerant leakage during use | 0.28 kgCO2e |
| B2: Maintenance (if information given by manufacturer) | N/A |
| B3: Repair | 266 kgCO2e |
| B4: Replacement | N/A |
| B5: Refurbishment | N/A |
| B6: Operational energy | N/A |
| B7: Operational water | N/A |
| C1: Refrigerant leakage when decommissioning | 0.01 kgCO2e |
| C2: Transport | 3 kgCO2e |
| C3: Waste processing | 21 kgCO2e |
| C4: Disposal | 1 kgCO2e |
| Embodied carbon results (kg CO2e) – without refrigerant leakage | |
| A1–C4 without buffer factor (excluding B1, C1) | 1908 kgCO2e |
| A1–C4 with buffer factor (excluding B1, C1) | 2480 kgCO2e |
| Embodied carbon result (kg CO2e) – refrigerant leakage only | |
| B1 (refrigerant leakage during use) + C1 (refrigerant leakage at end of life) | 0 kgCO2e |
| Embodied carbon result with 'mid-level' calculation method – total | |
| Result of 'mid-level' calculation method | 2,505 kgCO2e |
| Assumptions | |
| A1: Material carbon coefficient source | CIBSE TM65, Table 2.1 |
| B1: Refrigerant annual leakage rate (%) | N/A |
| C1: Refrigerant end of life recovery rate (%) | N/A |
| B3: Materials replaced as part of repair (%) | 76 |
| C4: Percentage of product going to landfill (%) | 55 |



CONTACT US

hello@impact-loop.com ↗

WEBSITE

impact-loop.com ↗

SOCIAL

[LinkedIn](#) ↗

© 2024 ImpactLoop [Terms & Conditions](#) [Privacy Policy](#)

This document, prepared by Join the Loop Ltd (trading as ImpactLoop). is intended for informational purposes only. While we have made every effort to ensure the accuracy and completeness of the information contained herein, we cannot guarantee its absolute accuracy. Join the Loop Ltd (trading as ImpactLoop) disclaims all liability for any errors or omissions, and for any direct or indirect damages arising from the use or reliance on this information. Specifications are subject to change without notice.

Page 3 of 3